-FUJIOH-

HOOD/ FR-SC2090























Immaculate Outside In

中も外も、キレイがつづく。

A fusion cooker hood of an ergonomic inclined design and easy cleaning feature bringing cleanliness to a revolutionized preeminent level. Your cooker hood has never been cleaner than before, both outside in.


ADVANCED FUNCTIONS



01/ Super Kirei Fan



- Eliminates the accumulation of oil and stain buildup on fan
- Repels and induces oil from cooking fumes to accumulate in oil tray
- Keeps fan and internal body of cooker hood clean for longer time



02/ Advanced Technology in Oil Capturing



- Oil separation process filtrates captured fumes into oil
- Oil flows into the oil tray with the help of rectifier panel, aqua slit filter and sirocco fan

04/ Ergonomic Inclined Design





- Sleek and stylish design
- Lower positioning to hob helps in smooth and efficient absorption of cooking fumes

Oil does not stick

03/ Advanced Technology in Fume Capturing






- Adjustable suction from bottom of Rectifier Panel to improve suction power from upper, left, and right side
- Capture more fumes efficiently

05/ Easy Maintenance





Aqua Slit Filter

- Hydrophilic Coating
- The filter can be easily washed with only water

Oil Repellent Paint

- Oil repellent paint is processed on all surfaces
- Easy to wipe and clean

^{*3} years warranty for motor • 1 year warranty for other parts Warranty Terms and Conditions apply Product images are for illustrative purposes only and may differ from the actual product

-FUJIOH-

COLORS









*Product images are for illustrative purposes only and may differ from the actual product.

PARTS INCLUDED




Recycling Unit (Only for FR-SC2090R)




GFO-Duct Cover (Only for FR-SC2090V)

INSTALLATIONS



FR-SC2090R (Recycling) [mm]



FR-SC2090V (Ventilating) [mm]

SPECIFICATIONS

Туре	FR-SC2090R (RECYCLING)	FR-SC2090V (VENTILATING)
Material	(Body) SGCC (Switch Panel) Glass	
Dimensions [mm]	W900 x D544 x H490	W900 x D544 x H1045~1345
Weight[kg]	21	
Power Consumption [W] (220/230/240V)	160/170/180	
Voltage [V/Hz]	220-240/50	
Duct Diameter[mm]	-	Ф150
Air Flow [m³/h] (220/230/240V)	495/500/505	700/705/710
Sound Level [dB] (220/230/240V)	52/52/52	55/55/56
Oil Capturing Ratio [%]	92	85
Switch	Touch Switch	
Speed	3 Speeds	
Hood Body	Oil Repellent Paint	
Fan	Super Kirei Coating	
Rectifier Panel	Oil Repellent Paint	
Filter	Aqua Slit Filter (Hydrophilic Coating)	
Oil Tray	Oil Repellent Paint (External Surface)	
Lighting	LED 1.5W x 2	

^{*}All specification are based on stringent in-house test results conducted in Fuji Industrial Co. Ltd, Japan







