


GAS HOB/ **FH-GS70**



Double Happiness! ふたつの炎、ダブルの幸せ

Bid farewell to uneven cooking. The advanced feature of double inner flame promotes improvement in the even heat distribution and speeds up your cooking time.

The best of both worlds are in your hands! The seamless design integrates both the double inner flame burner as well as the external flame burner all in one, allowing you to have preference of cooking methods in one single gas hob. Your master chef dreams of yesterday becomes a reality with FH-GS70 today!



ADVANCED FUNCTIONS

01/ Double Inner Flame





More even heat distribution and faster cooking time



Rust-resistant aluminium alloy







Deflect and reduce thermal heat on the top plate and knobs



FH-GS7030 SVGL

FH-GS7030 SVSS





FH-GS7020 SVGL



FH-GS7020 SVSS

SPECIFICATIONS

Number of Burner	3	3	2	2
Color	Black Glass	Stainless Steel	Black Glass	Stainless Steel
	(Toughened Glass)	(SUS304)	(Toughened Glass)	(SUS304)
Dimensions [mm]	W880 x D520 x H171	W860 x D500 x H171	W780 x D460 x H171	W780 x D450 x H171
Ignition Type	Battery Operated	Battery Operated	Battery Operated	Battery Operated
	(Size D 1.5V)	(Size D 1.5V)	(Size D 1.5V)	(Size D 1.5V)

HEATING LOAD L.P. GAS [kW]

Left	4.5	4.5	4.5	4.5
Centre	1.1	1.1	-	
Right	5.0	5.0	5.0	5.0
All Burners On	10.6	10.6	9.5	9.5

HEATING LOAD TOWN GAS [kW]

Left	3.9	3.9	3.9	3.9	
Centre	1.1	1.1			
Right	4.1	4.1	4.1	4.1	
All Burners On	9.1	9.1	8.0	8.0	

CUT-OUT DIMENSIONS & REPLACEMENT SIZE [mm]


Cut-out Dimensions	W700 x D400	W700 x D400	W650 x D350	W650 x D350
Front Allowance & Rear Allowance	FA≥71 x RA≥74	FA≥65 x RA≥60	FA≥62 x RA≥73	FA≥62 x RA≥63
Replacement Size	W(700-800) x D(400-430), R50	W(700-800) x D(400-430), R50	W(650-720) x D(350-410), R50	W(650-720) x D(350-410), R50
Base Height	85	85	85	85

INSTALLATIONS

FH-GS7030 SVSS


FH-GS7020 SVGL


FH-GS7020 SVSS




FH-GS7030 SVGL

[Unit: mm]











global.fujioh.com

For enquiries, email fit@fujioh.com.sg | Telephone +65 6286 3286 Fax +65 6285 3285 | Service Hotline +65 6286 2284

FUJIOHSG O FUJIOHSG www.fujioh.com/sg

[Unit: mm]