

INSTANT WATER HEATER/ FZ-WH51

NAGI SERIES

凪シリーズ

Instant warmth, instant comfort

すぐに温かく、ほっと緩む。

Experience the Calm - where every shower becomes a moment of serenity.

Say goodbye to temperature fluctuations and hello to effortless comfort. With precise control at your fingertips, set your ideal shower temperature with the turn of the knob.

Designed for smooth operation and a powerful water flow, it transforms your daily routine into pure relaxation. Step in, unwind, and embrace a new level of comfort.





FEATURES

WATER HEATER

01/ Performance & Control



Smart Temperature Stability



Digital Temperature Control



90° Stop Valve with Built-in Filter



DC Motor#



Powerful Flow

Deliver powerful flow while saving up to 70% energy



Quieter Operation

Operates with less noise than conventional AC pumps



Maintenance-Free with Brushless Design

No carbon brushes to replace for easier upkeep and longer lifespan

02/ Safety & Protection



Fire Retardant Heater Unit



Anti-Leak Water Unit



Thermal Cut Off



IP26 Splash Proof Protection



Error Monitoring System



Auto Flow Sensor Switch



Insulated PVC Hose

03/ Ease-of-Use & Comfort



Stepless Power Control



Color Variation



Adjustable Rain Shower Height^



Multi-Spray Hand Shower









Mistv



^{*5} years warranty for heater unit • 1 year warranty for other parts Warranty Terms and Conditions apply

-FUJIOH-

COLORS

INSTALLATIONS


01/ Hand Shower Set Type



FZ-WH5133N BK/ Black (Matte) FZ-WH5133D BK/ Black (Matte)



FZ-WH5133N W/ White (Glossy) FZ-WH5133D W/ White (Glossy)




02/ Rain Shower Set Type





Product images are for illustrative purposes only and may differ from the actual product. The dimensions of both types of heaters are identical.

02/ Rain Shower Set Type



SPECIFICATIONS

Model	FZ-WH5133N	FZ-WH5133D	FZ-WH5133DR	
Equipment				
Water Connection [mm/inch BSP]	1/2"	1/2"	1/2"	
Brushless DC Silent Inverter Pump	No	Yes	Yes	
Adjustable Rain Shower Height	No	No	Yes	
Performance				
Minimum Water Flow Rate [Liter/min]	2			
Maximum Water Pressure [kPa]	380 (55 psi)	380 (55 psi)		
Minimum Water Pressure [kPa]	20 (2.9 psi)			
Power, Voltage				
Voltage [V/Hz]	230/50			
Available Power [kW]	3.3			
Accreditation				
Safety Standard	IEC 60335-2-35:2012 + A1:2016+A2:2020			
Energy Efficiency	Singapore Standard 646 : 2019			
	100 210-m	45 224m	1 20 mm	
ROSH	YES (Based on part suppliers declaration)			
ISO Certified Manufacturer	ISO:9001:2015			
Dimensions and Weight				
Dimensions of Heater [mm]	W220 x H390 x D89			
Net Weight(Heater only) [kg]	1.6	1.7	1.7	
Gross Weight(Heater+Shower Set only) [kg]	2.9	3.5	5.5	

For enquiries, email fit@fujioh.com.sg | Telephone +65 6286 3286 Fax +65 6285 3285 | Service Hotline +65 6286 2284

