MULTIFUNCTIONAL STEAM OVEN/

FV-ML75























LIMITED WARRANTY*

Steam Cooking, Reinvented with Dual Convection. パワフルな蒸気が作る、驚きの一皿。

Cleaning is just as effortless. The Blue Ceramic coated cavity resists grease everyday cooking.



-FUJIOH-

ADVANCED FUNCTIONS

01/ Dual Convection Fans



Enhances thermal efficiency for even cooking

02/ Dual Temperature Control



Separate settings for top and bottom heating elements for precise cooking control

03/ Double Steam **Outlets**



Ensures rapid steam release for faster and more even steaming

-FUJIOH-


COLORS

INSTALLATIONS

FUNCTIONS

ACCESSORIES





4

[Unit: mm]

STEAM

• LOW TEMP STEAM • MID TEMP STEAM
• HI TEMP STEAM

BAKE

DATE

LOW HUMIDITY STEAM + BAKE

MID HUMIDITY STEAM + BAKE

HI HUMIDITY STEAM + BAKE

TOP + BOTTOM

DUAL TEMPTOP + BOTTOM

TOP + BOTTOM + FAN

CONVECTION

CONVECTION

DUBLE GRILL



STEW

FRY

• STEW

AUXILIARY

**BREAD **
**AUTO MENU **
**PROVING **
**PROVING **
**DEFROST **
**QUICK PREHEAT **
**KEEP WARM **
**DRYING **
**DESCALE **
**STEAM CLEAN



Product images are for illustrative purposes only and may differ from the actual product.

SPECIFICATIONS

General Model Name		FV-ML75
Туре		Built-in Multifunctional Steam Oven
Performance Highlights Functions Cooking Functions Auto Cook Menu		Dual Convection Fan, Dual Temperature Control, Double Steam Outlets
		24
		20
		30
Temperature Range [°C]	Min / Max	30 - 250
	Bake	50 - 250
	Grill	50 - 230
	Steam	50 - 150
	Fry	120 - 230
	Stew	110 - 150
		73
Cavity Material		Stainless Steel + Blue Ceramic Coating
Display Information		LED Display
Control Type		Touch Switch
Integrated Cleaning System	า	Steam Clean
Water Tank Type		One-Touch Auto Flap
Water Tank Capacity [ml]		1200
Rack Positions		5
Soft Close Door		No
ion Safety Features		Auto Lock, Water Shortage Alarm, Error Monitoring System
Glass Door Layers		3
Technical Information Dimensions [mm] Cut-Out Size / Dimensions [mm] Weight [kg] Voltage [V/Hz] Ampere Required [A] [Based on 230V]		W595 x D550 x H595
		W560 x D555 x H590
		38
		220, 230, 240/50
		15
Rated Power Consumption [W]	[W]	3200
Ratea i ower consumption		
	Type Highlights Functions Cooking Functions Auto Cook Menu Temperature Range [°C] Cavity Capacity [L] Cavity Material Display Information Control Type Integrated Cleaning System Water Tank Type Water Tank Capacity [ml] Rack Positions Soft Close Door Safety Features Glass Door Layers Dimensions [mm] Cut-Out Size / Dimensions Weight [kg] Voltage [V/Hz] Ampere Required [A] [Base	Type Highlights Functions Cooking Functions Auto Cook Menu Temperature Range [°C] Min / Max Bake Grill Steam Fry Stew Cavity Capacity [L] Cavity Material Display Information Control Type Integrated Cleaning System Water Tank Type Water Tank Capacity [ml] Rack Positions Soft Close Door Safety Features Glass Door Layers Dimensions [mm] Cut-Out Size / Dimensions [mm] Weight [kg] Voltage [V/Hz] Ampere Required [A] [Based on 230V]

For enquiries, email fit@fujioh.com.sg | Telephone +65 6286 3286 Fax +65 6285 3285 | Service Hotline +65 6286 2284



